

Sharp machine tools

PRECISION LATHES: SH1440



ONE-PIECE BASE CASTING

AVAILABLE IN SINGLE PHASE OR THREE PHASE

The SHARP SH1440 lathe is exceptionally heavy and rigid for its size. The bedway width is 10½". These machines feature a 1 9/16" spindle bore. **The base casting is one piece - from end to end.** The bedways and headstock gears are precision hardened and ground and the fully enclosed quick change gearbox allows a full range of inch and metric threading. A clutch overload system protects the apron feeds.

STANDARD EQUIPMENT

- Digital Readout**
- Taper Attachment**
- 3 Jaw Chuck
- 4 Jaw Chuck
- Steady Rest
- Follow Rest
- Multi Position Feed Stops
- Safety Brake
- Coolant System
- Splash Guard

SPECIFICATIONS

		SH-1440
Swing	- Over Bed	14"
	- Over Gap	20"
	- Over Slide	8 ½"
Bed	- Width	10 ½"
	- Length	40"
Spindle	- Speeds	12: 40 RPM – 1800 RPM
	- Bore "	1.57" (40mm)
	- Nose	Camlock D1-4
	- HP	3 HP
Threads	- Inch	4 to 112 TPI
	- Metric	7.5 mm to .45 mm
Tailstock	- Taper	4 MT
	- Travel	4"
Net Weight:		2,200 lbs.

Specifications are subject to change